

From Bindings to Branding -



## **Triumph Cutter 5560**

MARL5560

This MBM Triumph 5560 21%" Programmable Hydraulic Paper Cutter has a comprehensive SCS safety package: patented EASY CUT electronic blade activation bars for true two-hand operation; IR light beam safety curtain on front table; safety cover on rear table; lockable main switch; automatic blade and clamp return from every position; blade changing device covers cutting edge of blade; blade depth adjustment from outside of machine; blade and cutting stick can be changed without removing covers.



Easy to Use

Patented EASY CUT blade activation bars ensure true, two handed operation and allow blade and clamp to be activated independently.







VANCOUVER BC 604.574.9508



5560

Triumph Cutter

## Features

- Triumph 5560 offers a high storage capacity, programmable EP back gauge control module with 10 button keypad and LED display stores 99 programs (up to 99 steps each) and frequently used measurements
- Programmable control unit features repeat cut and eject functions
- Up to 9 repeat cuts can be integrated into a program in a single step | Digital measurement readout in cm or inches (accurate to 1/10 mm or 1/100 inch)
- "Set" function key for reference measurement
- Self-diagnostic system with error indication on display
- Electric, spindle-guided back gauge drive
- Electronic hand wheel with variable speed control for manual back gauge setting
- Bright, LED optical cutting line
- Precision swing-cut blade movement
- Hydraulic blade and adjustable hydraulic clamp drive
- The Triumph 5560 clamp is guided on both sides to apply even pressure along entire cutting width and is fully adjustable between 1,900 and 3,800 psi
- False clamp and foot pedal allows for pre-clamping
- HSS Solingen steel blade
- Solid steel blade carrier and adjustable blade guides
- MBM provides a comprehensive "SCS" safety package
- Durable stainless steel work surface, front and rear
- All-metal construction

S	SPEC
215/8"	Cutting Width
3¾" (3½" with false clamp)	Cutting Height
3¾" (3½" with false clamp)	Narrow Cut
227/16"	Back Gauge
hydraulic	Blade Drive
adjustable hydraulic	Clamp Type
digital display (cm/inch)	Measurement
yes	Cutting Indicator
IR light beam safety curtain	Table Safety
yes	Blade Bars
yes	Tool Holder
side tables	Accessories
55" x 42" x 54"	Dimensions
970 lbs	Weight
115 V / 60 Hz	Electrical Req.
2 hp	Motor Output



