



SOUTHWEST BUSINESS PRODUCTS LTD.

— From Bindings to Branding —



HLA-2301/HLA-2501 Automatic Laminator

MARLHLA2301 / MARLHLA2501

The newest, commercial-grade Fujipla laminator by Dry-Lam has everything you know and love about the previous ALM line for automatic feeding, laminating, trimming, and stacking sheets, but is now faster and better with improved features and functionality! Laminating up to 68" per minute, it is 25% faster than the ALM3230.



Improved film roll installation

Proprietary chip-reading design automatically sets to the correct temperature for the film in use. Both HLA-2301 and HLA-2501 models include a stand with waste basket to collect scraps.

HALIFAX NS
902.477.0382

MONTREAL QC
514.694.7741

OTTAWA ON
613.744.7004

TORONTO ON
416.285.7044

CALGARY AB
403.717.1707

VANCOUVER BC
604.574.9508

Features

- Ultra-quick warm-up time of up to less than 5 minutes
- Automatic single or double-sided lamination
- 2 Automatic trim options:
 - Flush-cut: precise, micro-adjustable with up to ± 3 mm margin adjust (HLA-2301)
 - Border-cut: custom-sealed options with 4-sided trim uniformity
- Hands-free, automatic feed tray
- Simple operation with specially encoded film for auto settings

Specially formulated film

- Strong adhesion with no peeling or bubbling, even on flush-cut sheets
- Proprietary chip-reading design
- Automatically sets to the correct temperature for the film in use



SPECS

HLA: 2301 vs 2501	HLA-2301	HLA-2501
Laminating Width	12.6"	
Speed	68" per minute	20-67" per min
Film Thickness (mil)	1.5 - 10 (10 mil single-side only)	1.2, 1.5, 3, 5
Laminating Thickness	16 mil	16 mil
Paper Thickness	17lb bond - 100lb cover (64-240 gsm)	17lb bond - 80lb cover (64-209 gsm)
Heat Type	Heated rollers, dual heat only	
Temperature Range	170 - 270°F	
Warm-up Time	Less than 5 minutes	~6.5 minutes
Paper Sizes	8.5"x5.5" 8.5"x11" 11"x17" 12"x18" 13"x19"	8.5"x5.5" 8.5"x11" 12"x18"
Paper Feed Capacity	200 sheets	
Trimming Methods	Flush cut or border cut	
Margin Adjust	Front: -1.2" +1" Back: -1" +1.2" (-25 to +30mm)	
Slitter Fine-Tuning	± 3 mm	± 5 mm
Operation Panel	Colour LCD display	
Included	Stand, Feeder Tray and Extension, Rear Tray, Power Cord, Manual, Waste Bin	
Electrical Req.	100-240 VAC, 50-60Hz	
Dimensions (LxWxH)	48" x 23.5" x 44"	49" x 23" x 19.5"
Laminator Weight	170 lbs	93 lbs