

model overview

Shrink Wrapping Machines



	18"/24" Shrink Wrapper Bar Sealer	Tabletop L Bar Sealer with work table	MP-2 Sealer With Tunnel	MP-3 Auto Sealer With Tunnel	All-In-One 12"x18.5" Shrink Wrapper	All-In-One 12"x18.5" Shrink Wrapper	Economy Series 15"x19" without tunnel	Economy Series 15"x19" With Tunnel	Economy Series Automatic
Roll Width Capacity	18"/24"	12"/18"	18"	18"	20"	24"	20"	22"	20"
Machine Direction	Right to Left	Right to Left	Right to Left	Right to Left	Right to Left	Right to Left	Right to Left / Left to Right	Right to Left	Right to Left
Wraps Per Min	6-8	6-8	14	14	4-6	6-8	6-8	8-12	8-12
Temperature Control	-	-	•	•	•	•	•	•	•
Seal Time Control	-	-	-	•	•	•	•	•	•
Variable Speed Belt Conveyor	-	-	-	•	-	-	•	•	•
Dual Blower Motor/Heater System	-	-	•	•	-	-	•	•	•
Dual Magnet Clamping	-	-	-	-	•	•	•	•	•
Re-Circulating Air Chamber	-	-	-	-	-	-	-	•	•
Auto Tunnel Cooldown and Shutoff	-	-	-	-	-	-	-	•	•
Micro Knife Technology	-	-	•	•	-	-	-	•	•
Pin Wheel Punch	-	-	•	•	•	•	•	•	•
Anti Jam Feature	-	-	-	-	-	-	-	•	•
Volts	120 V	120 V	220 V	220 V	220 V	220 V	120 V	120 V	220 V
Amps	9 Amp	9 Amp	16 Amp	16 Amp	20 Amp	25 Amp	15 Amp	20 Amp	40 Amp
Machine Weight, pounds	20/30	95/106	500	600	270	350	200	460	450
Shrink Tunnel Dimensions (D x W x H), inches	-	-	24"x16"x9"	24"x16"x9"	max height 6"	max height 8"	-	20"x16"x6"	28"x18"x8"
Sealing Area Dimensions (D x W), inches	-	-	14"x18"	14"x19"	12"x18.5"	16"x22"	15"x19"	15"x19"	16"x22"
Machine Dimensions (D x W x H), inches	30" x 20" x 10" / 30" x 30" x 10"	21" x 19" x 13" / 22" x 29" x 24"	22"x79"x30"	22"x79"x30"	50"x26"x45"	56"x30"x45"	40"x40"x26"	76"x26"x50"	104"x31"x61"

Plastic Shrink Wrap

Southwest Business carries shrink wrap film in a range of widths, lengths and gauges. Ranging from 12" to 18" in 60 gauge x 4375 ft. or 75 gauge x 3500 ft., we have stock on hand for fast delivery. Speak to us about all your shrinkwrapping film requirements.



Width	Code	Thickness	Roll Length
12"	POSH12X75	75 Gauge	3,500ft
14"	POSH14X60	60 Gauge	4,375ft
	POSH14X75	75 Gauge	3,500ft
16"	POSH16X60	60 Gauge	4,375ft
	POSH16X75	75 Gauge	3,500ft
18"	POSH18X60	60 Gauge	4,375ft
	POSH18X75	75 Gauge	3,500ft
20"	POSH20X60	60 Gauge	4,375ft
	POSH20X75	75 Gauge	3,500ft

[See back for our Shrink Wrap Film Information >](#)



Micro Knife Technology

Micro-Knife technology uses teflon coated single piece band ribbon located in upper seal bar. Will seal PVC or polyolefin films without smoke or residue.



Dual Magnet Clamping

Dual locking magnet clamps apply consistent pressure across seal bar



Pin Wheel Hole Punch

Adjustable pin perforator provides air evacuation



Variable Speed Belt Conveyor

The conveyor speed of the shrink tunnel can be adjusted to properly heat a shrink film



Film Cradle

Heavy duty film cradle allows for quick and easy adjustment and changeover



Temperature Control

Simple, easy to use control panel with automatic cycle timing and adjustable temperature setting.